

## Cable Specification

Offered Cable: **AT-5BE1CTT-048 + Cu pair**

**LT DryBlock, 48 vl. AW FLEX (OD cable 10,8 mm), Cu pair**

Basic Cable Details: Loose Tube cable  
 Diel. CSM  
 HDPE Sheath (thickness 1,5 mm) with Aramid Yarns Rovings  
 UV stable Sheath  
 2 Ripcords  
 4x12 fibers AllWave FLEX  
 1 x Cu pair

5 tube positions      4 tubes by 12 fibers AllWave FLEX  
 1 Cu pair

### Tube Color Coding

Fibre Count:	Tube 1	Tube 2	Tube 3	Tube 4	Tube 5
48	Blue 12F	Orange 12F	Green 12F	Brown 12F	Cu pair*

Cable Sheath Marking: **AT-5BE1CTT-048 Cu pair** mm-yy xxxx m  
 - where mm-yy is month and year of manufacturing, xxxx is length mark in meters

Offered Amount:

Cable Diameter (calc.): 10,80 mm

Cable Weight (calc.): 90 kg/km

Ship tolerance: 0% to 2% (the reels should not be shorter then specified)

Additional requirements: the customer requires the measurement protocol to be submitted with the reels and also separately by e-mail before cable shipment.

