

Montážní tabulka pro AT-5BE27DT-048-COAE

Námrazová oblast: I-0

Vodorovna složka namáhání [MPa]: 20,0

Namáhání vodiče [MPa]

rozp/tepl	-40	-30	-20	-10	0	10	20	30	40	-5+z
74	20.85	20.61	20.36	20.12	19.88	19.63	19.39	19.15	18.91	23.32
75	20.85	20.6	20.36	20.12	19.88	19.64	19.4	19.16	18.92	23.39
76	20.85	20.6	20.36	20.12	19.88	19.64	19.4	19.16	18.92	23.46
77	20.84	20.6	20.36	20.12	19.88	19.64	19.4	19.16	18.92	23.52
78	20.84	20.6	20.36	20.12	19.88	19.64	19.4	19.16	18.92	23.59
79	20.84	20.6	20.36	20.12	19.88	19.64	19.4	19.16	18.93	23.66
80	20.84	20.6	20.36	20.12	19.88	19.64	19.4	19.16	18.93	23.72

Průhyb vodiče [m]

rozp/tepl	-40	-30	-20	-10	0	10	20	30	40	-5+z
74	0.31	0.31	0.32	0.32	0.33	0.33	0.33	0.34	0.34	0.76
75	0.32	0.32	0.33	0.33	0.34	0.34	0.34	0.35	0.35	0.77
76	0.33	0.33	0.34	0.34	0.34	0.35	0.35	0.36	0.36	0.79
77	0.34	0.34	0.34	0.35	0.35	0.36	0.36	0.37	0.37	0.81
78	0.35	0.35	0.35	0.36	0.36	0.37	0.37	0.38	0.38	0.83
79	0.35	0.36	0.36	0.37	0.37	0.38	0.38	0.39	0.39	0.85
80	0.36	0.37	0.37	0.38	0.38	0.39	0.39	0.4	0.4	0.87